

## Legacy AP1000 Trigger Guns



The World's most popular and easiest to repair trigger gun!!!



- **PSI: 4500**
- **GPM: 12**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 19 oz

| Part No.    | Original No. | Description                      |
|-------------|--------------|----------------------------------|
| 9.802-229.0 | 353010       | AP1000                           |
| 8.710-414.0 | 353010W      | AP1000 Weep                      |
| 8.704-157.0 | 109856       | Unitized Valve                   |
| 8.704-158.0 | 109857       | Unitized Valve (Weep)            |
| 8.704-159.0 | 109858       | Trigger Seal Kit                 |
| 8.916-530.0 |              | Case of 45 - AP1000 Trigger Guns |

Power performance with comfort and durability.



- **PSI: 5000**
- **GPM: 11.5**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 23 oz

| Part No.    | Original No. | Description      |
|-------------|--------------|------------------|
| 8.710-416.0 | 353025       | Model 2500       |
| 8.704-173.0 | 109950       | Unitized Valve   |
| 8.704-174.0 | 109960       | Trigger Seal Kit |

Extra value!



- **PSI: 4000**
- **GPM: 8**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 13.4 oz



| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-417.0 | 353030       | MV2005      |

## M407 Trigger Gun



- **PSI: 4000**
- **GPM: 7**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 13.4 oz

| Part No.    | Description         |
|-------------|---------------------|
| 8.750-247.0 | M407 Trigger Gun    |
| 8.750-456.0 | M407 Gun Repair Kit |

## MV 920 Gun



- **PSI: 4000**
- **GPM: 7**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 17 oz

| Part No.    | Description |
|-------------|-------------|
| 8.710-420.0 | Model 920   |
| 8.749-249.0 | Repair Kit  |

## Linear Trigger Guns



Superior quality inline gun, especially well suited for high reach applications.



- **PSI: 4000**
- **GPM: 10.5**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 21.9 oz

Linear

| Part No.    | Original No. | Description             |
|-------------|--------------|-------------------------|
| 8.710-439.0 | 353201       | Linear 2 Gun            |
| 8.704-141.0 | 109797       | Repair Kit-Linear 2 Gun |

## Giant Trigger Guns



The Original "Heavy weight".



- **PSI: 5000**
- **GPM: 10**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 29.28 oz

| Part No.    | Original No. | Description           |
|-------------|--------------|-----------------------|
| 8.710-394.0 | 352290       | 21290C - Brass Outlet |
| 8.710-392.0 | 352250       | 21250B - SS Outlet    |
| 8.722-172.0 | 6021227      | Repair Kit            |

# GUNS & LANCES

## MV 950 Gun



- **PSI: 4500**
- **GPM:** 8
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 20 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-423.0 | 353045       | Model 950   |
| 8.704-194.0 | 110030       | Valve Kit   |

## PA Trigger Guns



RL20

- **PSI: 3200**
- **GPM:** 8
- **Temperature:** 320°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 10 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-440.0 | 353207       | RL20        |
| 8.704-180.0 | 109993       | Repair Kit  |

## Suttner Trigger Guns



High pressure and fatigue free "relax action" design.



- **PSI: 5000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 21 oz

ST-2605

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-376.0 | 352219       | ST-2605        |
| 8.701-673.0 | 089850       | Unitized Valve |

Extreme durability with easy pull trigger.



ST-2305

- **PSI: 5000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 21 oz

| Part No.    | Original No. | Description                |
|-------------|--------------|----------------------------|
| 8.710-386.0 | 352238       | ST-2305                    |
| 8.710-387.0 | 352239       | ST-2300 w/ Weep (4500 PSI) |
| 8.701-673.0 | 089850       | Unitized Valve             |
| 8.701-674.0 | 089851       | Unitized Weep Valve        |

## Suttner Trigger Guns (continued)

15° offset angle thru gun for easier overhead use.

The handle style for "Big Hands".



- **PSI: 5000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 26 oz

ST-2000

| Part No.    | Original No. | Description         |
|-------------|--------------|---------------------|
| 8.710-388.0 | 352240       | ST-2000             |
| 8.701-663.0 | 089614       | Unitized Valve      |
| 8.701-665.0 | 089631       | Unitized Weep Valve |

The perennial favorite for general pressure washer applications.



ST-1500

- **PSI: 5000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 20.5 oz

| Part No.    | Original No. | Description         |
|-------------|--------------|---------------------|
| 8.710-384.0 | 352235       | ST-1500             |
| 8.710-385.0 | 352236       | ST-1500 w/ Weep     |
| 8.701-663.0 | 089614       | Unitized Valve      |
| 8.701-665.0 | 089631       | Unitized Weep Valve |

15° offset angle thru gun for easier overhead use.



ST-601

- **PSI: 4000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 23 oz

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-370.0 | 352201       | ST-601         |
| 8.701-663.0 | 089614       | Unitized Valve |

Relax action design, **STAINLESS STEEL** gun.



ST-2700

- **PSI: 5000**
- **GPM:** 12
- **Temperature:** 300°F
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 21 oz

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-389.0 | 352243       | ST-2700        |
| 8.701-658.0 | 089070       | Unitized Valve |

**Suttner Trigger Guns (continued)**

Relax action design



**ST-2620**

- **PSI: 1800**
- **GPM: 21**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 1.30 lb

| Part No.    | Original No. | Description             |
|-------------|--------------|-------------------------|
| 8.723-666.0 | 87236660     | ST-2620                 |
| 8.723-667.0 | 87236670     | ST-2720 Stainless Steel |

Excellent for truck and fleet washing applications



**ST-810 POM**

- **PSI: 2000**
- **GPM: 8**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: .82 lb

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-372.0 | 352210P      | ST-810 Gun  |

**Ceramic Unitized Ball Valve**



- Ceramic ball
- Highly resistant against nearly all soaps and acids
- Will fit in ST-2300, 2305, 2605, 2700 spray guns as a repair kit

| Part No.    | Description                 |
|-------------|-----------------------------|
| 8.749-907.0 | Ceramic Unitized Ball Valve |

**PA Trigger Guns**



**RL30 – YG5000**

- **PSI: 5000**
- **GPM: 10.5**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 26 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-377.0 | 352221       | RL30–YG5000 |
| 8.704-616.0 | 111976       | Repair Kit  |

**PA Trigger Guns (continued)**



**Vega 5000**

- **PSI: 5000**
- **GPM: 10.5**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 27.5 oz

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-378.0 | 352222-5     | Vega 5000      |
| 8.710-379.0 | 352222W      | Vega Weep Gun  |
| 8.704-232.0 | 110550       | Valve Kit Vega |
| 8.704-615.0 | 111950       | Repair Kit     |

Easy Hold Trigger, Stainless Steel Compensating.



**Orange Nova**

- **PSI: 6400**
- **GPM: 10.5**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 30 oz

| Part No.    | Original No. | Description            |
|-------------|--------------|------------------------|
| 8.904-098.0 | 353223       | Orange Nova SS Gun     |
| 8.704-617.0 | 111980       | Repair Kit Orange Nova |

Easy pull and easy to hold with matching blue lance.



**RL-55 Blue & Lance**

- **PSI: 5650**
- **GPM: 8**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" BSP outlet
- Weight: 23.3 oz
- Blue vent grip, stainless steel lance has 1/4" BSP threads



| Part No.    | Original No. | Description                    |
|-------------|--------------|--------------------------------|
| 8.710-446.0 | 353250       | RL-55 Blue Gun                 |
| 8.710-645.0 | 368440PB     | 40" SS lance w/ blue vent grip |
| 8.704-610.0 | 111814       | Repair Kit- RL-55              |

# GUNS & LANCES

## Mecline Guns

Easy Pull, Easy Hold!



AL 35

- **PSI: 5000**
- **GPM: 8**
- **Temperature: 302°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 20 oz

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-434.0 | 353110       | AL 35 - Black  |
| 8.710-435.0 | 353111       | AL 35 - Yellow |
| 8.720-563.0 | AL016650016  | Repair Kit     |

Easy pull trigger.



AL 19

- **PSI: 4500**
- **GPM: 8**
- **Temperature: 302°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 20 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-433.0 | 353105       | AL 19       |
| 8.720-563.0 | AL016650016  | Repair Kit  |



AL 5

- **PSI: 4060**
- **GPM: 10.5**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 25 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-432.0 | 353100       | AL 5        |
| 8.720-561.0 | AL01165006   | Repair Kit  |

## MV Hobby Wash Gun



Excellent Light-duty gun.



- **PSI: 1850**
- **GPM: 5**
- **Temperature: 180°F**
- 1/4" M inlet x 1/4" F outlet
- Weight: 8.4 oz

Hobby Wash Gun

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-419.0 | 353040       | Hobby Wash Gun |

NOTE: See page 16 for Hobby Unit parts

## Big Guns



Model RL124

- **PSI: 1950**
- **GPM: 32**
- **Temperature: 210°F**
- 1/2" FPT inlet / outlet
- Weight: 44 oz



Model RL204

- **PSI: 3200**
- **GPM: 53**
- **Temperature: 320°F**
- 3/4" F inlet / 1/2" outlet
- Weight: 47.5 oz

| Part No.    | Original No. | Description              |
|-------------|--------------|--------------------------|
| 8.723-874.0 |              | Model RL124              |
| 8.740-165.0 |              | Model RL204              |
| 8.725-421.0 |              | Repair Kit - Model RL124 |
| 8.749-327.0 |              | Repair Kit - Model RL204 |
| 8.704-136.0 | 109775       | Repair Kit - Model 100   |
| 8.704-612.0 | 111900       | Repair Kit - Model 160   |



Model RL84 "Big Black Gun"

- **PSI: 7250**
- **GPM: 21**
- **Temperature: 210°F**
- 1/2" SS FPT inlet / outlet
- Weight: 60.3 oz



ST-3002 Stainless Steel Gun

- **PSI: 7250**
- **GPM: 26**
- **Temperature: 300°F**
- 1/2" plated steel FPT inlet / outlet
- Weight: 42.5 oz



| Part No.    | Original No. | Description                    |
|-------------|--------------|--------------------------------|
| 8.710-445.0 | 353246       | Model RL84                     |
| 8.750-459.0 |              | Repair Kit                     |
| 8.710-380.0 | 352223       | ST-3002                        |
| 8.701-677.0 | 089876       | Repair Kit (Includes Seal Kit) |
| 8.701-676.0 | 089875       | Seal Kit                       |

## Big Stainless Steel Lances & Side Handles

For big guns shown above.



- **PSI: 4050**
- **Temperature: 300°F**

- High pressure stainless steel pipe
- Complete with adjustable handle & coupler for 1/4" MPT nozzle
- 1/2" MPT gun connection
- Schedule 40 pipe

| Part No.    | Original No. | Description  |
|-------------|--------------|--|
| 8.904-081.0 | 352902A      | 20" Wand w/ Handle   |
| 8.904-083.0 | 352904A      | 40" Wand w/ Handle   |
| 8.904-086.0 | 352906A      | Side Handle Only   |
| 8.710-411.0 |              | 39", SS, 8700 PSI 300°F<br>Inlet 1/2" MNPT, Outlet 1/4" MNPT |

## Open Guns

Durable Glass Reinforced Handle.



- **PSI: 4000**
- **GPM: 12**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Tubular Flow-Thru internals for high pressure and efficiency
- Weight: 16.7 oz

AP-1000 Open Gun

| Part No.    | Original No. | Description            |
|-------------|--------------|------------------------|
| 8.710-396.0 | 352600       | Legacy AP1000 Open Gun |

## Open Guns

Just plain comfortable!



- **PSI: 4500**
- **GPM: 12**
- **Temperature: 302°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 21.5 oz

| Part No.    | Original No. | Description |
|-------------|--------------|-------------|
| 8.710-398.0 | 352602       | Open Gun    |



AP-740 Open Gun

| Part No.    | Original No. | Description    |
|-------------|--------------|----------------|
| 8.710-425.0 | 353050       | AP740 Open Gun |

## Flow Thru Guns



- Pistol grip gun handle
- Tough polyurethane insulation
- Cushion grip - red or black
- Full grip or slim line handle (See specs below)

### Gun Handle only

| Part No.    | Original No. | Description                         |
|-------------|--------------|-------------------------------------|
| 8.710-399.0 | 352605       | Full Red Grip 3/8" FPT x 1/4" FPT   |
| 8.710-400.0 | 352606       | Full Black Grip 3/8" FPT x 1/4" FPT |

### Gun Handle w/ 18" Lance

| Part No.    | Original No. | Description                   |
|-------------|--------------|-------------------------------|
| 8.710-403.0 | 352614       | Slim Red Grip 1/4" M x 1/4" F |
| 8.710-404.0 | 352616       | Full Red Grip 3/8" F x 1/4" M |

## AP Dump Gun

Water continues to run through the tube even when trigger gun is closed.



- **PSI: 3000**
- **GPM: 10.5**
- **Temperature: 140°F**
- 3/8" FPT inlet x 1/8" FPT outlet

AP Single Barrel Dump Gun

| Part No.    | Original No. | Description        |
|-------------|--------------|--------------------|
| 8.710-405.0 | 352810       | Dump Gun 16" Lance |
| 8.710-406.0 | 352812       | Dump Gun 40" Lance |
| 8.704-169.0 | 109905       | Repair Kit         |

## Dump Gun

Industrial duty dual-barrel.



- **PSI: 3000**
- **GPM: 10**
- **Temperature: 200°F**
- 3/8" FPT inlet x 1/4" FPT outlet

Dual Barrel Dump Gun

| Part No.    | Original No. | Description            |
|-------------|--------------|------------------------|
| 8.710-408.0 | 352820       | Dump Gun w/ 36" Barrel |
| 8.700-311.0 | 075296       | Repair Kits            |

# GUNS & LANCES

## Dual Lances



**Interpump Dual Lance**

- **PSI:** 3000
- **GPM:** 10
- **Temperature:** 220°F
- Excellent for down stream injector
- Zinc-plated for chemical resistance
- Brass & stainless steel valve w/ Viton seals
- Side handle valve adjustment

| Part No.     | Original No. | Description         |
|--------------|--------------|---------------------|
| 8.710-612.0  | 368150       | 36" Standard        |
| 8.710-621.0  | 368172       | 72" Extended        |
| 8.904-277.0* | 368151X      | 36" Deluxe Standard |
| 8.904-281.0* | 368173X      | 72" Deluxe Extended |
| 8.900-135.0  | 084072X      | Valve Repair Kit    |

## Dual Lances

Premium lance with stainless steel inserted seat.



**AL Premium Dual Lance**

- **PSI:** 3600
- **GPM:** 10.5
- **Temperature:** 302°F
- 1/4" tubing
- Vented grip
- 1/4" male inlet - female outlet



**AL Basic Dual Lance**

- **PSI:** 3600
- **GPM:** 10.5
- **Temperature:** 302°F
- 1/4" male inlet - female outlet
- 1/8" Zinc plated tubes
- Square molded grip inlet

| Part No.     | Original No. | Description                                     |
|--------------|--------------|---|
| 8.710-722.0  | 368925       | Stainless Steel Pipe                            |
| 9.803-267.0  | AL8355VPKIT  | Repair Kit                                      |
| 8.710-724.0  | 368927       | Basic Dual Lance                                |
| 8.720-548.0  | AL004650300  | Repair Kit                                      |
| 8.904-360.0* | 368926X      | AL Premium Deluxe w/Quick Coupler & Soap Nozzle |

## \*Deluxe Lances

Include Hardened Steel QC Inlet Plug, 1/8" 40 x 65 degree Soap Nozzle and Top Quality Quick Coupler. See lances with deluxe noted above.



## Suttner Dual Lances



**ST-54 w/ Side Handle**

**ST-53 w/ Knob**

- **GPM:** 10
- **Temperature:** 300°F
- Zinc / chromate finish
- 38" total length
- Molded grip
- High pressure thin wall tubing
- Weight: 42 oz

| Part No.    | Original No. | Description                     |
|-------------|--------------|---------------------------------|
| 8.710-613.0 | 368153       | ST-53 w/ Knob (4000 PSI)        |
| 8.710-614.0 | 368154       | ST-54 w/ Side Handle (4500 PSI) |
| 8.701-594.0 | 086884       | Repair Kit (ST-53)              |
| 8.900-153.0 | 086883X      | Clamp Kit (ST-53/54)            |
| 8.701-602.0 | 086907       | Repair Kit (ST-54)              |

## Suttner Push & Pull Lance



Vented grip can be pushed and pulled up to 90 degrees. For hard to reach applications, such as gutters, fenders, trucks, and heavy equipment.



- 3050 PSI
- 300°F
- 34" SS lance

| Part No.    | Original No. | Description             |
|-------------|--------------|-------------------------|
| 8.710-711.0 | 368880       | ST-85 Push & Pull Lance |

## Dual Trigger Lance

**Unique Design** – Go from High Pressure to Low Pressure (Rinse to Soap) with a pull of the trigger. Use with separate Trigger Gun or as an Open Gun, and still change from High to Low.



- **PSI:** 3600
- **GPM:** 12
- **Temperature:** 300°F
- Zinc-plated steel tubes
- Stainless steel seat
- Includes nozzle protector
- Weight: 39 oz

| Part No.    | Original No. | Description            |
|-------------|--------------|------------------------|
| 8.710-617.0 | 368158       | 48" Dual Trigger Lance |
| 8.900-781.0 | 109490       | Seal Kit               |

## Legacy Superlite SS Dual Lance



Superlite stainless steel with nozzle guard.



### Dual Lance w/ Nozzle Guard

- **PSI:** 4000
- **Temperature:** 200°F

- Side handle/ Valve actuator
- Viton seal
- Forged brass valve body
- 1/4" MPT inlet
- 1/8" SS outlet tubing

| Part No.    | Original No. | Description   |
|-------------|--------------|---------------|
| 8.710-618.0 | 368160       | 36" - 37.8 oz |
| 8.710-620.0 | 368165       | 72" - 56.0 oz |
| 8.900-781.0 | 109490       | Seal Kit      |

## PA Insulated Molded Grip Lances Round Daisy Grip



- **PSI:** 4000
- **Temperature:** 300°F
- Zinc-plated high pressure tubing
- Glass-filled Polyimide grips

- 1/4" MPT both ends
- Round daisy grip
- Better heat dispersion
- Reduced weight

| Part No.    | Original No. | Length            |
|-------------|--------------|-------------------|
| 8.710-657.0 | 368712PA     | 12" - Single Grip |
| 8.710-661.0 | 368720PA     | 20" - Single Grip |
| 8.710-665.0 | 368724PA     | 24" - Single Grip |
| 8.710-668.0 | 368728PA     | 28" - Single Grip |
| 8.710-672.0 | 368736PA     | 36" - Single Grip |
| 8.710-676.0 | 368748PA     | 48" - Double Grip |
| 8.710-681.0 | 368760PA     | 60" - Double Grip |
| 8.710-682.0 | 368778PA     | 79" - Triple Grip |

NOTE: For 15° bend at Lance Discharge, Place "BND" at end of the Original Part Number

## Square Molded Grip Lances



- **PSI:** 4500
- **Temperature:** 300°F
- Polyimide square grip
- 1/4" MPT both ends
- Bright Zinc-plated Steel

| Part No.    | Original No. | Length |
|-------------|--------------|--------|
| 8.710-655.0 | 368712A      | 12"    |
| 8.710-659.0 | 368720A      | 20"    |
| 8.710-663.0 | 368724A      | 24"    |
| 8.710-666.0 | 368728A      | 28"    |
| 8.710-670.0 | 368736A      | 36"    |
| 8.710-674.0 | 368748A      | 48"    |
| 8.710-678.0 | 368760A      | 60"    |
| 8.710-684.0 | 368779A      | 79"    |

NOTE: For 15° bend at Lance Discharge, Place "BND" at end of the Original Part Number

## MV Lance Handle



- Use on all 1/4" lances
- Easily positioned without removal of nozzle

| Part No.    | Original No. | Description       |
|-------------|--------------|-------------------|
| 8.704-162.0 | 109873       | 1/4" Lance Handle |

## AP Uninsulated Lances



Stainless steel or corrosion-resistant bright zinc-plated lances made with 1/4" tubing.

- **PSI:** 4100
- **Temperature:** 300°F
- Superior strength rolled threads
- 1/4" high pressure, lightweight, thin wall tubing

| Part No.               | Original No. | Length |
|------------------------|--------------|--------|
| <b>Stainless Steel</b> |              |        |
| 8.710-623.0            | 368212       | 12"    |
| 8.710-624.0            | 368220       | 20"    |
| 8.710-625.0            | 368224       | 24"    |
| 8.710-626.0            | 368228       | 28"    |
| 8.710-627.0            | 368236       | 36"    |
| 8.710-628.0            | 368248       | 48"    |
| 8.710-629.0            | 368260       | 60"    |
| 8.710-630.0            | 368278       | 78"    |
| <b>Zinc-plated</b>     |              |        |
| 8.710-631.0            | 368312       | 12"    |
| 8.710-632.0            | 368320       | 20"    |
| 8.710-633.0            | 368324       | 24"    |
| 8.710-634.0            | 368336       | 36"    |
| 8.710-635.0            | 368348       | 48"    |
| 8.710-636.0            | 368360       | 60"    |
| 8.710-637.0            | 368378       | 78"    |

NOTE: For 15° bend at Lance Discharge, Place "BND" at end of the Original Part Number

## Lance Handles / Accessories

Vented Grip, Side Handle with Nut and Vented Grip with Side Handle can be user-attached to Uninsulated Lances or 1/4" Steel Pipe – Detachable & Reusable.



| Part No.    | Original No. | Description               |
|-------------|--------------|---------------------------|
| 8.710-717.0 | 368909P      | Vent Grip Only (14" long) |
| 8.904-357.0 | 368909PS     | Grip with Side Handle     |
| 8.904-358.0 | 368920P      | Side Handle with Nut      |



| Part No.    | Original No. | Description                    |
|-------------|--------------|--------------------------------|
| 8.710-716.0 | 368909       | Vent Grip Only (14" long) ST-9 |
| 8.710-719.0 | 368911       | Grip with Side Handle          |
| 8.710-720.0 | 368920       | Side Handle with Nut           |

# GUNS & LANCES

## AP Lances w/ Oval Grips

10% Lighter weight reduces operator fatigue. Stainless steel or Zinc-Plated.



- **PSI:** 4100
- **Temperature:** 300°F
- 1/4" MPT both ends
- Tough glass-filled Polyimide
- Molded-on solid oval

| Part No.               | Original No. | Length | Description |
|------------------------|--------------|--------|-------------|
| <b>Stainless Steel</b> |              |        |             |
| 8.710-638.0            | 368412       | 12"    | Single Grip |
| 8.710-640.0            | 368420       | 20"    | Single Grip |
| 8.710-641.0            | 368424       | 24"    | Single Grip |
| 8.710-642.0            | 368428       | 28"    | Single Grip |
| 8.710-643.0            | 368436       | 36"    | Single Grip |
| 8.710-646.0            | 368448       | 48"    | Double Grip |
| 8.710-648.0            | 368460       | 60"    | Double Grip |
| 8.710-650.0            | 368479       | 79"    | Double Grip |
| <b>Zinc-plated</b>     |              |        |             |
| 8.710-656.0            | 368712M      | 12"    | Single Grip |
| 8.710-660.0            | 368720M      | 20"    | Single Grip |
| 8.710-664.0            | 368724M      | 24"    | Single Grip |
| 8.710-667.0            | 368728M      | 28"    | Single Grip |
| 8.710-671.0            | 368736M      | 36"    | Single Grip |
| 8.710-675.0            | 368748M      | 48"    | Double Grip |
| 8.710-679.0            | 368760M      | 60"    | Double Grip |
| 8.710-685.0            | 368779M      | 79"    | Double Grip |

NOTE: For 15" bend at Lance Discharge, Place "BND" at end of the Original Part Number

## Suttner Solid Insulated Molded Grip Lances



- **PSI:** 5800
- Glass-Filled Polyimide Grip
- Zinc-Plated High Pressure Steel Tubing
- 1/4" MPT Both Ends

| Part No.    | Original No. | Length |
|-------------|--------------|--------|
| 8.710-654.0 | 368712       | 12"    |
| 8.710-662.0 | 368724       | 24"    |
| 8.710-669.0 | 368736       | 36"    |
| 8.710-673.0 | 368748       | 48"    |
| 8.710-677.0 | 368760       | 60"    |
| 8.710-683.0 | 368779       | 79"    |

NOTE: For 15" bend at Lance Discharge, Place "BND" at end of the Original Part Number

## Adjustable Nozzle Holder



- **PSI:** 5700 / **GPM:** 10
- Perfect for cleaning hard to reach areas like inside containers or gutters
- Nozzle position locks with pressure
- **Temperature:** 300°F
- Stainless Steel
- 1/4" female inlet

| Part No.    | Description      |
|-------------|------------------|
| 8.749-905.0 | Outlet 1/4" FNPT |
| 8.749-906.0 | Outlet 1/4" Male |

## AP Vent Grip Lances

Stainless steel or zinc-plated lances with 1/4" inlet/outlet.



- **PSI:** 4100
- **Temperature:** 300°F
- Tough, reusable molded nylon vented handles for heat dissipation
- Heat venting hollow insulators
- 1/4" nozzle protector INCLUDED
- 1/4" male inlet – female outlet

| Part No.               | Original No. | Length          |
|------------------------|--------------|-----------------|
| <b>Stainless Steel</b> |              |                 |
| 8.710-688.0            | 368820SS     | 20" Single Grip |
| 8.710-691.0            | 368824SS     | 24" Single Grip |
| 8.710-697.0            | 368836SS     | 36" Single Grip |
| 8.710-701.0            | 368848SS     | 48" Double Grip |
| 8.710-705.0            | 368860SS     | 60" Double Grip |
| 8.710-710.0            | 368879SS     | 79" Double Grip |
| <b>Zinc-plated</b>     |              |                 |
| 8.710-686.0            | 368820M      | 20" Single Grip |
| 8.710-690.0            | 368824M      | 24" Single Grip |
| 8.710-695.0            | 368836M      | 36" Single Grip |
| 8.710-699.0            | 368848M      | 48" Double Grip |
| 8.710-703.0            | 368860M      | 60" Double Grip |
| 8.710-708.0            | 368879M      | 79" Double Grip |

NOTE: For 15" bend at Lance Discharge, Place "BND" at end of the Original Part Number

## Spray-Flex™ Flex Wand

Gives easy access to difficult spots, great for cleaning engines, roofs, eaves or underneath almost anything! Holds its shape under pressure.



- **PSI:** 3000 & 5000
- **Temperature:** 190°F
- 90° flexibility

| Part No.    | Original No. | PSI  |
|-------------|--------------|------|
| 8.710-597.0 | 368117       | 3000 |
| 8.710-596.0 | 368116       | 5000 |

## Flex Lances

Flexes a full 180° and returns, saving broken wand repairs.



- **PSI:** 2000
- **Temperature:** 200°F
- Prevents bent lances & broken hose
- Industrial grade polyurethane flex section
- Perfect for self-serve car wash bays
- 1/4" galvanized pipe end sections

| Part No.    | Original No. | Description              |
|-------------|--------------|--------------------------|
| 8.710-598.0 | 368118       | 18", 1/4" MPT x 1/4" MPT |
| 8.710-603.0 | 368121       | 21", 1/4" MPT x 1/8" FPT |
| 8.710-604.0 | 368124       | 24", 1/4" MPT x 1/8" FPT |

### Gutter Cleaner Attachment

Easily quick connect to any lance or extension wand to clean gutters or hard to reach areas. Angle improves reach and expands cleaning capabilities.



- **PSI:** 3500
- **Temperature:** 200°F
- Zinc Plated
- Inlet 1/4" M plug
- Inlet 1/4" F QC

| Part No.    | Description           |
|-------------|-----------------------|
| 8.711-324.0 | 1/4" Nipple x 1/4" QC |

### Extension Wand Control Kit



8.749-848.0

- Effortlessly raise and lower the wand using the water pressure
- Adjustable pressure
- No kick back or whipping action
- Easy grip handle
- Easy to install and control
- Right or left hand adjustable
- Durable, reliable, and light weight
- Reduce fatigue and time on the job

| Part No.    | Description                |
|-------------|----------------------------|
| 8.749-848.0 | Extension Wand Control Kit |



### Fiberglass Telescoping Wands



High quality telescoping wand reaches up to 24', 3 sizes to choose from. Lightweight and balanced under pressure.



Belt and pole clamp

- **PSI:** 3500
- **Temperature:** 200°F
- 6' - 12' Wand shown

| Part No.                | Original No. | Length                        | PSI  | Description |
|-------------------------|--------------|-------------------------------|------|-------------|
| 8.710-589.0             | 368090       | 6' - 12'                      | 3500 | Long!       |
| 8.710-590.0             | 368091       | 6' - 18'                      | 3500 | Longer!!    |
| 8.710-591.0             | 368092       | 8' - 24'                      | 3500 | Longest!    |
| 8.700-059.0             | 056008       | Strap & Belt Shoulder Harness |      |             |
| <b>Replacement Guns</b> |              |                               |      |             |
| 8.723-896.0             |              | TS12 Replacement Gun          |      |             |
| 8.710-595.0             | 368098       | TS18 Replacement Gun          |      |             |
| 8.739-434.0             | 368099       | TS24 Replacement Gun          |      |             |

# GUNS & LANCES

## X-Jet Long Range Nozzle



8.710-474.0

- Projects water and chemical up to 40'
- Chemicals bypass pump, lance, hose and gun for damage protection
- Includes 15' hose with inline shut-off valve and color coded proportioners

| Part No.     | Original No. | Description                             | PSI       |
|--------------|--------------|---|-----------|
| 8.710-474.0* | 360103       | X-Jet Long Range Nozzle                 | 2000-3000 |
| 8.710-475.0* | 360104       | X-Jet Long Range Nozzle                 | 3000-4000 |
| 8.710-473.0  | 360102       | M5 X-Jet Variable Fan Long Range Nozzle | 2000-3000 |

\*Includes Close Range Nozzle

## Hobby Gun, Lance & Hose

Don't turn away hobby unit owners. Complete replacement hose, gun and lance!



8.711-285.0

8.711-531.0

9.802-223.0

| Part No.    | Original No. | Description                                   |
|-------------|--------------|---|
| 9.802-223.0 | 4-011137     | Insulated Lance w/ Gun                        |
| 9.802-220.0 | 4-011106     | Lance w/ Coupler (Not Shown)                  |
| 8.711-285.0 | 4-011105     | Lance w/ #3 Hi/Low Varifan Nozzle             |
| 8.711-531.0 | 4-02010025M  | 1/4" x 25' Thermoplastic Hose, 22mm both ends |

NOTE: See page 22 for more Hobby Hose

## Kew Replacement Accessories



- **PSI: 4000**
- **GPM: 10.5**
- **Temperature: 300°F**
- 3/8" F inlet
- Bayonet Quick Coupler Outlet

### Iride Kew Style

| Part No.    | Original No. | Description      |
|-------------|--------------|------------------|
| 8.710-427.0 | 353065       | Iride Kew Style  |
| 8.704-173.0 | 109950       | Unitized Valve   |
| 8.704-174.0 | 109960       | Trigger Seal Kit |



Bayonet Plug

- 416 Stainless Steel Plug attaches any 1/4" lance to Kew Guns

| Part No.    | Original No. | Description                 |
|-------------|--------------|-----------------------------|
| 8.710-903.0 | 373069       | SS Plug w/ set back threads |

## Pressure Washer Accessory Kit



### Kit 1 - 3000 PSI Includes:

- Teflon Tape
- Hose, 3000 PSI 3/8 x 50', R1, SoxSw
- QC Nozzle, SS 1/4" #4.0x15
- Coupler, 3/8" Female brass
- Wand, 18" M22 x 1/4" QC
- Gun, S2 3/8" Inlet, Lance w/M22 coupler

### Kit 2 - 5000 PSI Includes:

- Teflon Tape
- Hose, 5000 PSI 3/8 x 50', R2, SoxSw
- QC Nozzle, SS 1/4" #4.0x15
- Coupler, 3/8" Female brass
- Wand, 18" M22 x 1/4" QC
- Gun, S2 3/8" Inlet, Lance w/M22 coupler

| Part No.    | Description                     |
|-------------|---------------------------------|
| 8.903-454.0 | Pressure Washer Accessory Kit 1 |
| 8.903-455.0 | Pressure Washer Accessory Kit 2 |

**Replacement Accessories**



Astra Style

- **PSI: 4000**
- **Temperature: 300°F**



Iride Style

- M22 - 1 "O" Ring inlet (Standard)
- M22 - 2 "O" Ring outlet (Extended)

| Part No.                | Original No. | Description           |
|-------------------------|--------------|-----------------------|
| 8.710-428.0             | 353070       | Astra Style, 10.5 GPM |
| 8.710-429.0             | 353075       | Iride Style, 8 GPM    |
| <b>Maintenance Kits</b> |              |                       |
| 8.704-173.0             | 109950       | Unitized Valve        |
| 8.704-174.0             | 109960       | Trigger Seal Kit      |

**Extended Twist Seal Coupler**



- **PSI:** 3600
- **GPM:** 11
- **Temperature:** 300°F
- Double O-ring Seal
- Machined Brass Body
- High Impact Plastic Knob

| Part No.    | Original No. | Description                  |
|-------------|--------------|------------------------------|
| 8.709-535.0 | 331215       | Coupler - 1/4" FPT x 22 mm F |
| 8.709-555.0 | 331315       | Plug - 1/4" FPT x 22 mm M    |

**Tip Retainer**



- 18 mm Thread
- Fits vent grip lance
- See tip jet nozzles in nozzle section

| Part No.    | Original No. | Description  |
|-------------|--------------|--------------|
| 8.710-901.0 | 373065       | Tip Retainer |

**Tip-Jet Nozzle System**



Tip-Jet Tips

**"Tip-Jet" Nozzle Systems** are versatile nozzling systems for everyday or specialized applications.

- **PSI:** to 4000
- Neat & simple tip change
- Hardened stainless steel tips with vanes
- Strainers available
- Body components available in brass, zinc-plated steel or stainless steel

| Orifice Size | 0° Part No. | 0° Orig. No. | 15° Part No. | 15° Orig. No. | 25° Part No. | 25° Orig. No. | 40° Part No. | 40° Orig. No. |
|--------------|-------------|--------------|--------------|---------------|--------------|---------------|--------------|---------------|
| 3.0          | 8.708-016.0 | 253316       | 8.708-017.0  | 253317N       | 8.708-018.0  | 253318        | —            | —             |
| 4.0          | 8.708-019.0 | 253330       | 8.708-020.0  | 253331        | 8.708-021.0  | 253332        | 8.708-022.0  | 253333        |
| 4.5          | 8.708-023.0 | 253338       | 8.708-024.0  | 253339        | 8.708-025.0  | 253340        | 8.708-026.0  | 253341        |
| 5.0          | 8.708-027.0 | 253346       | 8.708-028.0  | 253348        | 8.708-029.0  | 253349        | 8.708-030.0  | 253350        |
| 5.5          | 8.708-031.0 | 253355       | 8.708-032.0  | 253357        | 8.708-033.0  | 253358        | 8.708-034.0  | 253359        |
| 6.0          | 8.708-035.0 | 253365       | 8.708-036.0  | 253367        | 8.708-037.0  | 253368        | 8.708-038.0  | 253369        |
| 6.5          | 8.708-039.0 | 253375       | —            | —             | 8.708-040.0  | 253377        | 8.708-041.0  | 253378        |
| 7.0          | 8.708-042.0 | 253383       | 8.708-043.0  | 253385        | 8.708-044.0  | 253386        | 8.708-045.0  | 253387        |
| 7.5          | 8.708-046.0 | 253392       | 8.708-047.0  | 253393        | 8.708-048.0  | 253394        | 8.708-049.0  | 253395        |
| 8.0          | 8.708-050.0 | 253400       | 8.708-051.0  | 253401        | 8.708-052.0  | 253402        | 8.708-053.0  | 253403        |
| 9.0          | 8.708-054.0 | 253415       | 8.708-055.0  | 253416        | 8.708-056.0  | 253417        | 8.708-057.0  | 253418        |
| 10.0         | 8.708-058.0 | 253456       | 8.708-059.0  | 253457        | 8.708-060.0  | 253458        | 8.708-061.0  | 253459        |